



NOTES:

1. ALL BUS SHELTERS ARE TO BE MANUFACTURED AND INSTALLED IN ACCORDANCE WITH DISABILITY DISCRIMINATION ACT 1992 (DDA) COMPLIANCE.
2. SEAT MUST BE AT 500mm HEIGHT FROM GROUND AND MADE OF RECYCLED PLASTIC (TYPE OF RECYCLED PLASTIC SHALL BE APPROVED BY COUNCIL REPRESENTATIVE PRIOR TO INSTALLATION).
3. SHELTERS WITH TOUGHENED GLASS INFILL TO BE COLOURED 'HERITAGE GREEN' OR WITH MESH INFILL TO BE COLOURED 'CHARCOAL' (APPROVED BY COUNCIL REPRESENTATIVE PRIOR TO APPLICATION).
4. BOTTOM PANEL TO BE 3mm SOLID GALVANISED POWDER-COATED STEEL PLATE OR MESH INFILL- 3mm GALVANISED POWDER-COATED PERFORATED SHEETING WITH 3mm DIAMETER PERFORATIONS.
5. TOP TWO (2) PANELS TO BE 6-10mm TOUGHENED GLASS OR MESH INFILL- 3mm GALVANISED POWDER COATED PERFORATED SHEETING WITH 3mm DIAMETER PERFORATIONS.

REFERENCES:

APPROVED:

D Hannah
 Manager Engineering Services
 Date: April 2008



STANDARD DETAIL
 BUS SHELTER
 STRUCTURAL DETAILS

DRAWING No:

CGG711

AMENDMENT:

0

VER	APPD.	DATE	AMENDMENT
0	APR 08	REVISIED AND REISSUED	